ELEQ mastering electricity worldwide

GSA120 – Bushing-type Current Transformer

The GSA120 is a cast-resin insulated bushing-type current transformer for indoor applications. They are suitable to put on cables or bus-bars. In case of higher voltage levels the primary conductor must be insulated according to the rated insulation levels. The cast resin insulated indoor bushing-type current transformer can be used up to 1,2 kV. The current transformer is maintenance-free and mountable in any position.



Technical specifications

Environmental conditions	
This product is designed to be safe under the following conditions:	
Location:	Indoor use
Ambient air temperature:	-5°C .. +40°C; other temperatures on request
Storage and transport temperature:	-25°C .. +50°C
Relative humidity:	5% .. 95%, non condensing
Altitude:	Max. 1000m above NN; at >1000m data required
Protection degree (secondary terminal):	IP20
Application conditions	
Standard:	IEC 61869-2/IEEE C 57.13; etc.
IEC 61768-2 specification:	
Rated short-time thermal current (Ith):	100 x In/1s, max. 100kA/1s, other duration on request
Rated dynamic current (Idyn):	2,5 x Ith
Continuous thermal current (Icth):	up to 200%
Rated insulation level:	1,2/6/-kV
Rated frequency:	50/60Hz
Class of insulation:	E
Rated primary current:	30A - 1250A
Rated secondary current:	1A or 5A; other options available on request
Rated output:	As required. For example 10VA, 15VA
Accuracy class:	As required. For example 0,2, 5P20
Secondary terminal:	Screw terminals M5 (max. 2,5Nm)

Ordering Specifications

For the customized design of your ELEQ GSA120 Current Transformer the following information is required:

Mandatory
- Rated primary current
- Rated secondary current
- Rated output
- Accuracy class
- Frequency

Optional
- Multi-core transformers are possible
- Terminal box sealable
- Other relevant requirements

Wiring diagram IEC 61869-2 e.g. single core



Dimensions



window size	X	Y	Z
A	60	75	90
B	90	105	120
C	120	135	150
D	150	165	180