

IGW A1 – Supporting-type Current Transformer

The IGW A1 is used for measurement and protection in applications. The cast resin insulated indoor supporting-type current transformer can be used up to 12 kV. The current transformer is maintenance-free and mountable in any position.



Ordering Specifications

For the customized design of your ELEQ IGW A1 Current Transformer the following information is required:

Mandatory

- Rated primary current •
- Rated secondary current
- Rated output
- Accuracy class
- Frequency

Optional

• Other relevant requirements

Wiring diagram IEC 61869-2



part of a smart world-

Technical specifications

Environmental conditions	
This product is designed to be safe	
under the following conditions:	
Location:	Indoor use
Ambient air temperature:	-5°C +40°C; other
Storage and transport temperature	
Relative humidity:	5% 95% non condensing
Altitude:	Max 1000m above NN: at
	>1000m data required
Protection degree (secondary	
terminal):	IP20
Application conditions	
Standard:	IEC 61869-2/IEEE C 57.13; etc.
IEC 61768-2 specification:	
Rated short-time thermal current (Ith):	100 x In/1s, max. 50kA/1s
Rated dynamic current (ldyn):	2,5 x lth, max. 125kA/1s
Continuous thermal current (lcth):	up to 200%
Rated insulation level:	12/28/75kV
Rated frequency:	50/60Hz
Class of insulation:	E
Rated primary current:	5A – 800A
Rated secondary current:	1A or 5A; other options available on request
Rated output:	As required.
	For example 2,5VA, 10VA, 30VA
Accuracy class:	As required.
	For example 0,2S, 5P10
Primary connection:	M12 (40Nm)
Secondary terminal:	Screw terminals M5 (max. 2,5Nm)

Dimensions

