

Order Form – MT440

Customer project name 	Customer reference number 	ELEQ ordernumber
--	--	---

Hardware configuration

Auxiliary power supply ☐ Universal: 24...300 Vdc, 40...276 Vac ☐ 400 Vac	Input frequency ☐ 50/60 Hz ☐ 400 Hz	Communication type ☐ Without ☐ RS232 ☐ RS485
---	--	--

Outputs

IO1 ☐ Without ☐ Analogue output ☐ Fast analogue output ☐ Solid-state relay output ☐ Electromechanical relay output	IO2 ☐ Without ☐ Analogue output ☐ Fast analogue output ☐ Solid-state relay output ☐ Electromechanical relay output	IO3 ☐ Without ☐ Analogue output ☐ Fast analogue output ☐ Solid-state relay output ☐ Electromechanical relay output	IO4 ☐ Without ☐ Analogue output ☐ Fast analogue output ☐ Solid-state relay output ☐ Electromechanical relay output
--	--	--	--

Output 1	Input quantity	Output quantity
Min.		
Med. 1		
Med. 2		
Max.		
☐	Free programmable	☐ mA ☐ V

Output 2	Input quantity	Output quantity
Min.		
Med. 1		
Med. 2		
Max.		
☐	Free programmable	☐ mA ☐ V

Output 3	Input quantity	Output quantity
Min.		
Med. 1		
Med. 2		
Max.		
☐	Free programmable	☐ mA ☐ V

Output 4	Input quantity	Output quantity
Min.		
Med. 1		
Med. 2		
Max.		
☐	Free programmable	☐ mA ☐ V

Inputs

Input	Voltage	Current	
Direct or	V	Direct or	A
Via VT	/ V	Via CT	/ A

☐ Shipversion (Bureau Veritas approval)

Configuration system connection*

Single phase connection (1b)	☐
Three phase three wire connection with balanced load (3b)	☐
Three phase three wire connection with unbalanced load (3u)	☐
Three phase four wire connection with balanced load (4b)	☐
Three phase four wire connection with unbalanced load (4u)	☐

Pulses
Pulse Output assigned to output (1, 2, 3 or 4):
Pulses per
☐ kWh
☐ MWh
Other

Alarm/trip
Assigned output (1, 2, 3 or 4):
Switch/trip at (input value):

Additional requirements

* The multifunctional transducer can be configured with user friendly setting software, MiQuen or by ELEQ on request.